

# BINKS Ram Unit

# **FLUID HANDLING**



# BINKS Ram Unit Packages

Binks new range of Ram Units offer a reliable and higher performance solution for the delivery of medium and high viscosity materials. Binks Ram Units provide the ideal delivery solution for materials such as lubricants, mastics, adhesives, epoxies, and sealants. They deliver a constant, low pulse flow of materials to the dispensing tool by ensuring correct priming of the pump and preventing material cavitation.

Complete Ram Units include an easy-use pneumatic control box with up/down switch, auto shut off when the container is empty and a release valve to break the suction seal when lifting the ram plate clear of the used material. Optional extras include an automatic Change Over switch for use with two Ram Units.


- Wide choice of pump ratios from 8:1 to 60:1 (ball-check) and 5:1 to 68:1 (chop-check)
- Patented Binks low-ice motors provide non-stop performance
- Pump rod and packings last up to 3X longer than the competition
- Stainless Steel pump fluid section as standard

#### **RAM PACKAGES**


SR20	DR20	DR30	DR60	DR205	DRX205	DRI205
Single Post Ram Unit with 3" pneumatic rams and 5 Gallon/20L Follower Plate. 6 pump options.  Cart mounted version available.	Dual Post Ram Unit with 3" pneumatic rams and 5 Gallon/20L Follower Plate. 13 pump options.	Dual Post Ram Unit with 3" pneumatic rams and 7.5 Gallon/30L Follower Plate. 13 pump options.	Dual Post Ram Unit with 3" pneumatic rams and 15 Gallon/ 60L Follower Plate.  13 pump options.	Dual Post Ram Unit with 3" pneumatic rams and 55 Gallon/ 205L Follower Plate. 24 pump options.	Dual Post Extreme Duty Ram Unit with 6" pneumatic rams and 55 Gallon/205L/15 Gallon/60L Follower Plate. 24 pump options.	Dual Post Air Intensified Ram and 55 Gallon/ 205L Follower Plate. 24 pump options.

#### **Ram Unit Pump Outfit Options**

Equip your Ram Unit from our extensive range of durable, hard-working MX Pumps. (See back page for pump fluid output and pressure ratings)




#### BINKS Ram Unit





#### BINKS Ram Units / Compatible Pump Specifications

### **Ram Unit Ball-Check Pump Options**




## Feature

		/	
Maximum Wo	6 Bar / 87 psi		
Air Pressure			
Air Inlet	1/2" BSP F		
	SR20	410 mm / 16"	
Ram	DR20/30/60	688 mm / 27"	
Stroke	DR205	960 mm / 37.8"	
	DRX205		
lluit llaimht	SR20	1242 mm / 49"	
Unit Height - Fully	DR20/30/60	1750 mm / 69"	
Extended	DR205	2550 mm / 100°	
Exterided	DRX205		
	SR20	EPDM / PU	
Wiper Ring	DR20/30/60		
Material	DR205	EDPM	
	DRX205		
NAT. 1. 1. 1	SR20	55 kg / 121 lbs	
Weight	DR20/30/60	130 kg / 286 lbs	
without	DR205	212 kg / 466 lbs	
Pump	DRX205		

#### **Ram Unit Chop-Check Pump Options**

1 = Available on SR20

2 = Available on DR20, DR30, DR60





#### **BINKS DX SERIES PUMP 5-YEAR WARRANTY**

BINKS® warrants to the original end-user purchaser that Binks® Ram-Unit products shall not fail under normal use and service due to a defect in material or workmanship within five (5) years from the date of shipment from Binks®. Does not include normal wear and tear.



SOLUTIONS FOR YOUR WORLD

www.carlisleft.com